

Product Description

Use high-performance COB LED, Ra>80. Aluminum heatsink and unique die casting heatsink design ensure better heat dissipation.

Luminaire

Structure	Fixed Down Light LED
Model No.	IBSP110
Wattage	10W 15W 25W
Luminous Flux	>900lm 1350lm 2250lm
Beam	15° 24° 38° 45°
IP Ratings	IP65
Material	Die casting aluminum heatsink
Finish	White black

Installation

Installation
Suitable for 5~18 mm thick ceiling board


LEDs

Brand	Bridgelux Cree
Type	COB
Color Temp	2700K 3000K 3500K 4000K 5000K 5700K 6000K 6500K
CRI	80 90


Control Gear

Remote constant current LED driver	
Brand	Eaglerise Lifud OEM
Input Voltage	220~240Vac 100-240Vac
Dimming	Non Dim Dim
Remarks	Flicker-free,PF 0.5 0.9

Photometrics



Ra>80



Job/Project

Location

Fixture Ref.

Quantity

Remarks

Picture



Line art

Unit: mm

Model	Watts	D xH(mm)	Cutout(mm)
IBSP110CT075H92	10W	Ø85×H92mm	Ø75mm
IBSP110CT075H113	15W	Ø85×H113mm	Ø75mm
IBSP110CT075H139	25W	Ø85×H139mm	Ø75mm