

Product Description

Use high-performance SMD LED, Ra>80. Aluminum heatsink and unique die casting heatsink design ensure better heat dissipation.

Luminaire

Structure	Fixed Down Light LED
Model No.	IBDL240
Wattage	15W 22W 32W
Luminous Flux	> 100lm/w
Beam	100°
IP Ratings	IP20
Material	Die casting aluminum heatsink
Finish	White black

Installation

Suitable for 5~18 mm thick ceiling board


LEDs

Brand	Osram Sanan Samsung
Type	SMD
Color Temp	2700K 3000K 3500K 4000K 5000K 5700K 6000K 6500K
CRI	80 90


Control Gear

Remote constant current LED driver	
Brand	Eaglerise Lifud
Input Voltage	220~240Vac 100-240Vac
Dimming	Non Dim Dim
Remarks	Flicker-free,PF 0.5 0.9

Photometrics



Ra>80



Job/Project

Location

Fixture Ref.

Quantity

Remarks

Picture



Line art

Model	Watts	D×H(mm)	Cutout(mm)
IBDL240CT120	15W	Ø135×H38mm	Ø125mm
IBDL240CT145	22W	Ø170×H38mm	Ø150mm
IBDL240CT215	32W	Ø228×H38mm	Ø200mm