

Job/Project _____
 Location _____
 Fixture Ref. _____
 Quantity _____
 Remarks _____

Product Description

Use high-performance COB LED, Ra>80. Aluminum heatsink and unique die casting heatsink design ensure better heat dissipation.

Luminaire

Structure	Fixed Down Light LED
Model No.	IBSP137
Wattage	8W 10W 15W
Luminous Flux	>400lm 500lm 750lm
Beam	15° 24° 38° 45° 60°
IP Ratings	IP65
Material	Die-casting alu. trim and heatsink, PMMA. lens
Finish	Matt white or black trim

Installation

Suitable for 5~18 mm thick ceiling board

LEDs


Brand	Bridgelux Cree
Type	COB
Color Temp	2700K 3000K 4000K 5000K 5700K 6500K
CRI	80 90

Control Gear


Remote constant current LED driver

Brand	Lifud Eaglerise OEM
Input Voltage	220~240Vac 100240Vac
Dimming	Non Dim Dim
Remarks	Flicker-free, PF 0.5 0.9

Photometrics




Ra>80



Picture



Line art



Model	Watts	D x H(mm)	Cutout(mm)
IBSP137CT055	8W	Ø 65×H76m	Ø 55mm
IBSP137CT075H69	10W	Ø 83×H69m	Ø 75mm
IBSP137CT075H90	15W	Ø 83×H90m	Ø 75mm