

Product Description

Use high-performance COB LED, Ra>80. Aluminum heatsink and unique die casting heatsink design ensure better heat dissipation.

Job/Project

Location

Fixture Ref.

Quantity

Remarks

Luminaire

Structure	Fixed Down Light LED
Model No.	IBSP101S
Wattage	8W 10W 15W 28W
Luminous Flux	> 720lm 900lm 1350lm 2520lm
Beam	15° 24° 38° 45° 60°
IP Ratings	IP65
Material	Die casting aluminum heatsink
Finish	White black

Installation

Installation
Suitable for 5~18 mm thick ceiling board


LEDs

Brand	Bridgelux Cree
Type	COB
Color Temp	2700K 3000K 3500K 4000K
CRI	5000K 5700K 6000K 6500K
CRI	80 90


Control Gear

Remote constant current LED driver	
Brand	Eaglerise Lifud OEM
Input Voltage	220~240Vac 100-240Vac
Dimming	Non Dim Dim
Remarks	Flicker-free,PF 0.5 0.9

Photometrics



Ra>80



Picture



Line art			
Model	Watts	D xH(mm)	Cutout(mm)
IBSP101SCT055	8W	L65×W65×H76mm	L55×W55mm
IBSP101SCT075H74	10W	L85×W85×H74mm	L75×W75mm
IBSP101SCT075H94	15W	L85×W85×H94mm	L75×W75mm
IBSP101SCT075H122	25W	L85×W85×H122mm	L75×W75mm
IBSP101SCT095	28W	L105×W105×H120mm	L95×W95mm