

Product Description

Use high-performance COB LED, Ra>80. Aluminum heatsink and unique die casting heatsink design ensure better heat dissipation.

Luminaire

Structure	Adjustable Down Light LED
Model No.	IBSP151S
Wattage	8W 10W 15W 25W
Luminous Flux	800lm 1000lm 1500lm 2500lm
Beam	15° 24° 36° 38° 45° 50° 60°
IP Ratings	IP65
Material	Die-casting alu. trim and heatsink, PMMA. lens
Finish	Matt white or black trim

Installation

Suitable for 5~18 mm thick ceiling board

LEDs


Brand	Bridgelux Cree
Type	COB
Color Temp	2700K 3000K 3500K 4000K 5000K 5700K 6500K
CRI	80 90

Control Gear



Remote constant current LED driver

Brand	Lifud Eaglerise BOKE
Input Voltage	220~240Vac 100-240Vac
Dimming	Non Dim Dim
Remarks	Flicker-free, PF 0.5 0.9

Photometrics




Ra>80




Job/Project _____
 Location _____
 Fixture Ref. _____
 Quantity _____
 Remarks _____

Picture



Line art



Unit: mm

Model	Watts	LxWxH(mm)	Cutout(mm)
IBDL151SCT075H72	8W	L85xW85xH72	L75xW75
IBDL151SCT075H76	15W	L85xW85xH76	L75xW75
IBDL151SCT075H67	10W	L105xW105xH67	L95xW95
IBDL151SCT075H88	15W	L105xW105xH88	L95xW95
IBDL151SCT075H114	25W	L105xW105xH114	L95xW95