

Product Description

Use high-performance COB LED, Ra>80. Aluminum heatsink and unique die casting heatsink design ensure better heat dissipation.

Luminaire

Structure	Fixed Down Light LED
Model No.	IBSP112
Wattage	10W 15W 25W
Luminous Flux	>1000lm 1500lm 2500lm
Beam	15° 24° 38° 45° 60°
IP Ratings	IP65
Material	Die-casting alu. trim and heatsink, PMMA. lens
Finish	Matt white or black trim

Installation

Suitable for 5~18 mm thick ceiling board

LEDs


Brand	Osram Sanan
Type	COB
Color Temp	2700K 3000K 3500K 4000K 5000K 5700K 6500K
CRI	80 90

Control Gear

Remote constant current LED driver


Brand	Lifud Eaglerise OEM
Input Voltage	220~240Vac 100-240Vac
Dimming	Non Dim Dim
Remarks	Flicker-free,PF 0.5 0.9

Photometrics




Job/Project _____
Location _____
Fixture Ref. _____
Quantity _____
Remarks _____

Picture



Line art



Unit: mm

Model	Watts	D xH(mm)	Cutout(mm)
IBSP112CT085H48	10W	Ø 100×H48mm	Ø 80mm
IBSP112CT085H68	15W	Ø 100×H68mm	Ø 80mm
IBSP112CT085H96	25W	Ø 100×H96mm	Ø 80mm