

Job/Project \_\_\_\_\_  
 Location \_\_\_\_\_  
 Fixture Ref. \_\_\_\_\_  
 Quantity \_\_\_\_\_  
 Remarks \_\_\_\_\_

## Product Description

Use high-performance COB LED, Ra>80. Aluminum heatsink and unique die casting heatsink design ensure better heat dissipation.

## Luminaire

Structure Adjustable Down Light LED  
 Model No. IBSP138  
 Wattage 10W | 15W | 25W  
 Luminous Flux > 900lm | 1350lm | 2250lm  
 Beam 38° | 45°  
 IP Ratings IP65  
 Material Die casting aluminum heatsink  
 Finish White | black

## Installation

Installation  
 Suitable for 5~18 mm thick ceiling board


## LEDs

Brand Bridgelux | Cree  
 Type COB  
 Color Temp 2700K | 3000K | 3500K | 4000K  
 CRI 5000K | 5700K | 6000K | 6500K  
 CRI 80 | 90


## Control Gear

Remote constant current LED driver  
 Brand Eaglerise | Lifud | OEM  
 Input Voltage 220~240Vac | 100-240Vac  
 Dimming Non Dim | Dim  
 Remarks Flicker-free, PF 0.5 | 0.9

## Photometrics



Ra>80



## Picture



**Line art**

| Model            | Watts | D xH(mm)  | Cutout(mm) |
|------------------|-------|-----------|------------|
| IBSP138CT095H104 | 10W   | Ø105×H104 | Ø95        |
| IBSP138CT095H122 | 15W   | Ø105×H122 | Ø95        |
| IBSP138CT095H146 | 25W   | Ø105×H146 | Ø95        |